

TYPE W CABLE WITH INDUSTRY STANDARD ‘CAMLOCK’ STYLE CONNECTORS:

- UL Listed
- CSA Listed
- cULus listed
- Resists acids, alkalis, chemicals, heat, flame, oil and moisture
- Listed as Type RHH, RHW and RHW-2
- RoHS Compliant
- Temperature Range -40°C to + 90°C
Dry. 90°C Wet rating



APPLICATIONS

- Temporary cable for load bank testing
- Cabling for temporary power (i.e. with rollup generators)
- Installing temporary panels within a facility

AVAILABLE IN

- 50ft lengths with male and female camlocks
- Female and male “pigtails” with bare ends (approximately 3 feet in length)
- Female and male “pigtails” with compression lugs (approximately 3 feet in length)

SPECIFICATIONS

Gauge	Ampacity (free air)
4/0	400A
1/0	260A

BINS

Cables and associated bulk equipment are typically delivered in collapsible bins. Bins have forklift pockets so they can be easily moved with a pallet jack. Bin outside dimension are as follows:

	Width	Length	Height
Standard bin	45"	48"	34"
Mini bin	30"	32"	34"



ASSOCIATED ITEMS AVAILABLE FOR RENT



INSULATED MULTITAPS



EXTENSION
CORDS



CABLE RAMPS



MECHANICAL
LUGS



Ask us about our
Intelligent Load Bank Remote System
It turns multiple load banks into a single load bank system for commissioning

kWick Power Rentals, P.O. Box 358, Mamaroneck, NY 10543
P. (877) 383.4040 E. rent@kwickequip.com

