

120 VDC 'SUITCASE' STYLE PORTABLE LOAD BANK WITH THE FOLLOWING FEATURES:

- 500A at 120VDC (60kW)
- Super compact
- Includes adjustable potentiometer for fine tuning load
- Completely self-contained. No other power source required
- Shipped in heavy duty case



COOLING SYSTEM

Forced air-cooled by 9 x DC power driven muffin fans. Rated for continuous operation. No external power source required.

LOCAL OPERATOR CONTROL PANEL INCLUDING:

Digital metering for DC Volts, Amps & Watts. 2 meter test jacks. Rugged load toggle switches with main master load switch. Variable load switch for fine load adjustments.

SAFETY FEATURES

- Thermal cut-off switch drops load in event of overheating
- Single main fuse

CONSTRUCTION

Painted steel enclosure with convenient carrying handles. Load cables easily connected via color coded camlok connectors.

Voltage	Total Load (Amps)	Load Steps (Amps)
120 VDC	500 A	0-125 (variable), 125, 125, 125

BLUEPRINT & DIMENSIONS:

APPROXIMATE DIMENSIONS:
8"W x 22"D x 21"H
[203 X 559 X 533 mm]

APPROXIMATE WEIGHT:
58 LBS [26.3 kg]

MANUFACTURER:
Cannon Load Banks Inc.

CASE DIMENSIONS:
12.5"W x 24.5"D x 26"H
[318 X 622 X 660 MM]

APPROXIMATE WEIGHT (WITH LOAD BANK):
88 lbs [40 kg]

