

24/36/48 VDC 'SUITCASE' STYLE PORTABLE LOAD BANK WITH THE FOLLOWING FEATURES:

- 500A at 24 or 48VDC (12kW/24kW)
- 375A at 36VDC (12.6kW)
- Super compact
- Includes adjustable potentiometer for fine tuning load
- Completely self-contained. No other power source required
- Shipped in heavy duty case



COOLING SYSTEM

Forced air-cooled by 6 x DC power driven muffin fans. Rated for continuous operation. No external power source required.

SAFETY FEATURES

- Thermal cut-off switch drops load in event of overheating
- Single main fuse

LOCAL OPERATOR CONTROL PANEL INCLUDING

Analog metering for DC Volts and Amps. Power indicator lamp. 2 meter test jacks. Rugged load toggle switches with main master load switch. Variable load switch for fine load adjustments.

CONSTRUCTION

Painted steel enclosure with convenient carrying handles. Load cables connected to positive and negative copper terminals that protrude from the top of the unit.

Voltage	Total Load (Amps)	Load Steps (Amps)
24 VDC	500 A	0-100 (variable), 100, 100, 200
36 VDC	350 A	0-75 (variable), 75, 75, 150
48 VDC	500 A	0-100 (variable), 100, 100, 200

BLUEPRINT & DIMENSIONS:

APPROXIMATE DIMENSIONS:
8"W x 20"D x 11"H
[203 x 508 x 279 mm]

APPROXIMATE WEIGHT:
49 lbs [22.2 kg]

MANUFACTURER:
Cannon Load Banks Inc.

CASE DIMENSIONS:
12.5"W x 24.5"D x 16"H
[318 x 622 x 406 mm]

APPROXIMATE WEIGHT (WITH LOAD BANK):
64 lbs [29 kg]

